



Granulator/Refiner with compulsory feed (mechanic fuller)

Superior efficiency on all other granulator brand on the market

ADVANTAGES

- Safe
- Easy to operate, Reliable
- Need little maintenance



Model 954-AF

Granulator/Refiner :

Rotor: Heavy duty shaft. Machined, robust and very efficient rotor.

Hood: Equip with: - 1 electromechanical actuator for ease of operation when opening and closing hood.

Exit: Three (3) different bases of exit available : aspirator, conveyor, drawer

Rotary and anvil knives: Made with high impact steel

One abrasion resistant steel screen with a choice of hole size

Drive: 2 inertia wheels (one of this wheel is machined for a pulley 5V)

Safety limit switch prevent operation when servicing

Application : Compost, rubber, aluminium, copper, oil filter, PVC, plastic, polycarbonate, wood fibres



Model 309-AF

	Model 309-AF	Model 618-AF	Model 927-AF
Motor	20 or 30 H.P. 575 volts	50 or 60 H.P. 575 volts	75 or 100 H.P. 575 volts
Starter	20 or 30 H.P.	<i>Optionnal</i>	<i>Optionnal</i>
Rotary knives	Qty : 9	Qty : 18	Qty : 27
Anvil knives	Qty : 2	Qty : 4	Qty : 4
Grinding capacity	1,000 – 3,000 pounds/hr 454 – 1,363 kg/hr	2,000 – 6,000 pounds/hr 909 – 2,727 kg/hr	3,000 – 10,000 pounds/hr 1,363 – 4,545 kg/hr
Opening dimensions	11" x 14"	20" x 14"	29 1/2" x 14"
Overall dimensions	Height : 82 Width : 36" Length : 67"	Height : 80" Width : 48" Length : 73"	Height : 80" Width : 60" Length : 78"
Compulsory Feed (mechanic fuller) - Amps control - Augmentation of 30% on regular production	Motor/Transmission 1/2 H.P. 575 volts	Motor/Transmission 1 H.P. 575 volts	Motor/Transmission 1 1/2 H.P. 575 volts
Weight	3,000 pounds	5,300 pounds	6,300 pounds

Manufactured & sold by :



Beaver Products

6670, Rte 120 Lac Baker, N.-B. E7A 1N2
Tél. : 506-992-2356 Fax : 506-992-3926
pelletier@nb.aibn.com



Made in Canada
Fabriqué au Canada